

# TOUGH RELIABLE LONG-LASTING HAND PUMPS



## Ideal for use with drums and barrels in low volume applications.

As with all Fill-Rite® fuel transfer pumps, our hand pumps are tough, reliable and long lasting. Fill-Rite hand pumps are perfect for low volume transfer of gasoline\*, light oils, diesel fuel and other fluids from drums and barrels. Depending on the style of pump you choose, they operate by piston, rotary or hand lever action.

\*For use with the 100 and 5200 series only.



### Models available for a wide variety of fluids including:

- Diesel Fuel
- Bio Diesel
- Gasoline\*

- Motor Oil
- Automatic Transmission Fluid

- Hydraulic Oil
- And many other chemicals and light oils

### FILL-RITE.

### HAND PUMPS



### 5200 Piston Series · Heavy Duty

- For Drums, Totes, and Barrels
- Vaccum Breaker Included
- Cast Aluminum Housing Construction
- 2" NPT Bung Mount
- UL/cUL Certified

	Vaccum bleaker included Vaccum bleaker included				
R152	FR152	FR151	FR150		
Flow Rate (GPM/LPM)	20 Gal (75L) / 100 Strokes	20 Gal (75L) / 100 Strokes	20 Gal (75L) / 100 Strokes		
Inlet/Outlet	1" / 3/4"	1" / 3/4"	1" / 3/4"		
Compatibility	Gasoline, Diesel Fuel, Light Oil, and Kerosene				
Included Accessories	20" - 34 ¾" Steel	20" - 34 ¾" Steel	Pump Only		
	Telescoping Suction	Telescoping Suction			
	Pipe, ¾" x 8' Hose, ¾" Hose-end Spout	Pipe, Pail Spout			



#### 100 Rotary Series · Heavy Duty

- For Drums, Totes, and Barrels
- Vaccum Breaker Included
- Cast Aluminum Housing Construction
- 2" NPT Bung Mount
- UL/cUL Certified

FR112C	FR112	FR112C	FR113		
Flow Rate (GPM/LPM)	10 Gal (38 L) per 100 rev.	10 Gal (38 L) per 100 rev.	10 Gal (38 L) per 100 rev.		
Inlet/Outlet	1" / 3/4"	1" / 3/4"	1" / 3/4"		
Compatibility	Gasoline, Diesel Fuel, Light Oil, and Kerosene				
Included Accessories	20" - 34 ¾" Steel Telescoping Suction Pipe, ¾" x 8' Hose, ¾" Hose-end Spout	20" - 34 ¾" Steel Telescoping Suction Pipe, ¾" x 8' Hose, ¾" Hose-end Spout, Gallon Counter	20" - 34 ¾" Steel Telescoping Suction Pipe, Pail Spout		



#### Special Use Pumps · Standard Duty

- For Drums, Totes, and Barrels 2" NPT Bung Mount
- Will Handle a range of automotive fluids (see compatible fluids below)

SD65	FR31	FR20V	SD62	SD11
Description	Quart Stroke Pump	Lever Piston	Rotary Pump	Lever Piston
Flow Rate	1 Quart (1 Liter) per Stroke	11 oz. per Stroke	7.5 Gal (28 L) / 100 Strokes	11 oz. per Stroke
Inlet/Outlet	½" / Spout	1" / Spout	3/4"/Spout	1" / Spout with Garden Hose Threads
Matls of Const - Housing	Cast Iron and Steel	Polypropylene	Cast Iron	Steel and Cast Aluminum
Compatibility	Gear and Lube Oil, Petroleum Products, and Anti-freeze	Light Oils, Anti-freeze, Hydraulic Oils, and Coolant	Diesel, Kerosene, Machine Oil, and Petroleum Products	Light Oils, ATF, Diesel Fuel, Hydraulic Fluid, and Kerosene
Included Accessories	23" - 40½" Polypropylene Telescoping Suction Pipe	19¾" - 35½" Polypropylene Telescoping Suction Pipe	3 Pieces of 13" Steel Suction Pipe	18½" - 34½" Steel Telescoping Suction Pipe and No-Drip Valve



8825 Aviation Drive Fort Wayne, Indiana 46809 P(800) 634-2695 or (260) 747-7524 F (800) 866-4861

